

OVABOARD – PROTECT FLOORS AND AVOID RE-WORK

OVATAPE™ PVC CONSTRUCTION TAPE

DESCRIPTION

OVATAPE is made from tough conformable PVC film and has an easy unwind release coating for ease of application. It is coated one side with an aggressive rubber adhesive system that is designed to release off most surfaces.

BENEFITS

EASY TO USE: The smooth easy unwind release off the roll assists application and saves time.

AREAS OF USE

For jointing OVABOARD products, do not apply Ovatape to floor surfaces as it may affect some finishes.



TECHNICAL DATA:

COLOUR	ORANGE
Carrier	SOFT PVC FILM
Thickness (total)	0.127 MM
Adhesive	RUBBER
Adhesion to steel	0.40 kg/25mm
Tensile strength	5 kg/25
Elongation	150%
Roll size	48mm x 50m
Shelf life	12 months

ISO 9001 CERTIFIED MANUFACTURER.



SURFACE PREPARATION

The surface on which the tape is to be used must be clean, dry and free from grease and dust. We recommend testing on all surfaces before application to ensure suitability. Recommended application temperature is between 15° C and 25° C.

OVATAPE IS NOT VAPOR PERMEABLE, THEREFORE THE CURING RATE WHERE THE TAPE IS APPLIED OVER UNCURED CONCRETE SURFACES WILL VARY.

The statements in this information sheet are based upon our knowledge and practical experience. The data intended only as a source of information, is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications, customers should independently determine the suitability of this material for their specific purpose, prior to use.

GDP FLOORING SOLUTIONS LTD

PHONE 07 571 8003 | EMAIL INFO@GDPSOLUTIONS.CO.NZ
PO BOX 2378 TAURANGA 3140

www.ovaboard.co.nz

